
1626

COPPER FOIL SHEET

VentureTape® 1626 is a 1.2 mil electrolytic grade copper foil coated with a heat resistant acrylic adhesive. The copper foil is a uniformly high tensile alloy with carefully controlled dead soft temper, allowing for tight conformation to cut edges and cast surfaces. Designed for stained glass applications, VentureTape 1626 is individually packaged in sheets to protect the foil and provide easy self storage.

Product Construction



Features & Benefits

- · Individually packaged sheets for ease of use
- Excels in stained glass fabrication applications
- High performance acrylic adhesive performs well over a wide temperature range
- Robust, conformable copper foil is ideal for demanding stained glass applications
- In stock product available for immediate delivery

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness ^Ω	2.9 mils	0.07 mm	PSTC-133
Peel Adhesion △	50 oz/in	13.9 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	24 lb/in	108.5 N/25 mm	PSTC-131
Elongation	6 %	6 %	PSTC-131
Service Temperature	-40 to 225 °F	-40 to 107 °C	

 $[\]Omega$ - excluding liner

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

- Individually packaged; contact Venture tape for product packaging configurations
- Standard and custom roll sizes available; contact Venture Tape for specifications and requirements

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076 From United Kingdom 0-800-962-957 From Australia 1-800-122-797 www.venturetape.com



GTA - NHT, Inc.
Venture Tape
30 Commerce Rd., Rockland, MA 02370
Tel 781-331-5900; Fax 781-871-0065
800-343-1076 (U.S.A.), 800-544-1024 (Canada)
Toll Free Fax 877-264-5490
www.venturetape.com



^{△ - 20} minute dwell